PRODUCT INFORMATION



Dispenser UP

Metering and Mixing

Wolfangel dispenser and metering systems allow an economical use of your raw materials. You take the quantity you need and always in the right dosing ratio.

With the optional mixing head with hose and casting head you pour the material directly to your mould. Clean and easy without filling any buckets.

Standard:		
High quality piston pumps Separate outlets for resin and catalyst Catalyst recirculation	L-frame (150 cc on tripod) No flushing required	Accurate dosing of resin and catalyst Adjustable dosing lever
Options:		
Mixing head with static mixer Catalyst failure control PLC	Material hoses Cover to avoid manipulation	Casting head Pumps for additional components

Technical Data

(Subject to technical modifications!)



Dispenser 750 cc

Outlets for resin and catalyst

Dispenser	150	750	1000
Power		Compressed Air	
Pressure Ratio	1:1	2,5:1	1,75:1
Max. Air Pressure		6 bar	
Air Consumption	250 l/min	270 l/min	
Capacity per Double Stroke	150 cc	750 cc	1000 cc
Max. Output (dep. on viscosity)	~ 4.0 kg/min	~ 15.0 kg/min	~ 20.0 kg/min
Catalyst Dosing Ratio	0.7 – 3.4 %	1.4 – 3.5 %	1.0 – 2.8 %

www.wolfangel.com

WOLFANGEL GMBH - ROENTGENSTRASSE 31 - 71254 DITZINGEN / GERMANY - PHONE +49 7152 999200 - FAX +49 7152 58195 - EMAIL INFO@WOLFANGEL.COM