

Gelcoater with Airless External Mix

High pressure for a perfect part surface

Gelcoat spray technology made by Wolfangel means reliability and perfect results. The Gelcoater mini finds its place everywhere in your workshop due to the small size. Gelcoat and catalyst included.

Thanks to the high pressure external mixing gun you achieve outstanding micro porosity free surfaces. No flushing needed and therefore never again cured gelcoat guns.

Video: <http://youtu.be/DG3dGZvzeAM>



Gelcoater 44 cc

Gelcoater 150 cc

Standard:		
High quality piston pumps	L-frame (mobile machine (44 cc))	7.5 m hoses
No flushing required	Material recirculation	High pressure filter
Adjustable dosing lever	Place for gelcoat and catalyst (44 cc)	Vario nozzle

Options:		
Mobile cart(s)	Boom	Catalyst failure control
Quantity counter	Multi-colour machine	Hose extension

Technical Data

(Subject to technical modifications!)

Gelcoater	44	150
Power	Compressed Air	
Pressure Ratio	46:1	47:1
Max. Air Pressure	6 bar	
Air Consumption	270 l/min	1.100 l/min
Capacity per Double Stroke	44 cc	150 cc
Max. Output (dep. on viscosity)	~ 1.3 kg/min	~ 4.0 kg/min
Catalyst Dosing Ratio	1.0 – 3.5 %	1.0 – 3.4 %



Gelcoat-Gun AM with Vario-Nozzle

www.wolfangel.com

WOLFANGEL GMBH • ROENTGENSTRASSE 31 • 71254 DITZINGEN / GERMANY • PHONE +49 7152 999200 • FAX +49 7152 58195 • EMAIL INFO@WOLFANGEL.COM